

An ISO 9001: 2015 CERTIFIED ORGANISATION

MANUFACTURERS OF:

- Instrument Valves
- Manifold & Fittings
- Hydraulic Hose Pipe Fittings
- Flow Control Valves
- Ball Valves And Needle Valves









A.P. INDUSTRIES

INTRODUCTION

We are the manufacturers of "PRESSURE GAUGE ACCESSORIES, PROCESS INSTRUMENTATION VALVES & TUBE FITTINGS" since 2000.

Since we are manufacturing all these products with excellent quality without compromising quality at competitive prices for our esteemed products.

We have well equipped manufacturing unit with modern cnc machines with all testing facilities with experienced personal for controlling and maintaining quality of the products.

We manufacture all types of "pressure GAUGE ACCESSORIES, PROCESS INSTRUMENTATION VALVES & TUBE FITTINGS" in all materials i.e. A105, SS316, SS304, Monel 400/500, Hastelloy C276 material used in process instrumentation field.

Some of the products manufactured as stated below.

Gauge Cock, Needle Valve, Syphon, Snubber, Manifolds, Gauge Saver, Thermo Wells, Compression Fittings, Connectors, Condensate pot, Air header Non Return Valve, Ball Valves And Gate Valves.

We believe in best quality, speedy delivery, reasonable prices to cater our best services for today's industry..

MANIFOLD VALVES



Standard specifications:

Max. pressure: 400 bar/ 6000psi Max. Temp.: 240® C
Material: SS304 / SS316 Gland packing: PTFE

Std. process connection: ½" NTP (F) **Std. drain connection:** ¼" NPT (F)

A.P. INDUSTRIES





NEEDLE VALVES

Body construction by forged or bar stock. The complete range includes different instrument tube valves for different application.

Material grade: SS 304 / SS 316 Straight and angled body isolating or accurate metering. Used for liquid, gas, vapour analysis at high temperature.

Sizes: ½", 3/8", ½", ¾",1".

Threaded type: male -female, female-female, male-male, (BSP / NPT thread)



SNUBBER

SNUBBER / PULSATION DAMPERS Are Used To Protect Pressure Gauge From Sudden Pressure Changes And Fluctuation Of Pressurizing Fluid. Sudden Pressure Changes Are Dampened Before They Reach The Pressure Sensing Element To Minimize Stress It And Giving It Longer Life. These Find Applications In Hydraulic Machines, Compressors, Process Plants etc.

Material grade: SS 304 / SS 316

Sizes: 1/4" to 1" (male-female BSP/NPT Thread)

Working Pressure: Upto 400kgs.



BALL VALVE

Blow out proof bottom loaded stem. Low operating torque and with panel mounting facelifts. Floating ball design for positive sealing

Material grade: SS 304 / SS 316

Sizes: 1/4", 3/4", 1/2", 1" NTP (male-female BSP/NPT Thread)

Working Pressure: upto 10000 PSI.



SYPHON

Used for liquid, gas or vapour analysis at high temperature and high pressure.

Material grade: SS 304 / SS 316

Sizes: 1/4", 3/4", 1/2" (male-female BSP/NPT Thread)

Working Pressure: Upto 6000kgs.







CONDENSATE POT



NON RETURN VALVE



AIR HEADER



BRASS CONNECTOR



BRASS PIPE FITTINGS



FORGED PIPE FITTINGS



DOUBLE FERRULE FITTINGS



An ISO 9001: 2015 CERTIFIED ORGANISATION



HOSE PIPE FITTINGS

Address: Unit No. A 15/16, Lusi Industrial Estate, Oil Company Compound, Behind Modi Hyundai Showroom Village Waliv, Sativali Road, Vasai (E), Thane – 401208

SHOWIOUH VIHage VVally, Sativali Road, Vasai (E), Thane - 401200

Contact: 7350492926 / 7709582926 / 9175102926

Email: salesapindustries16@gmail.com / info@apindustries.net / enquiry@apindustries.net

Website: www.apindustries.net